

CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

MODEL L-65-N

PORTABLE LOAD BANK

THE L-65-N LOAD BANK is designed to provide a temporary load for field servicing and testing 120/240 volt single phase or 120/208 three phase 60HZ generators and inverters. This load bank is air cooled and completely self contained. The unit can load three phase 208VAC up to 50KW and 240VAC single phase up to 33.3KW. The unit can also load 120VAC up to 50KW.



MODEL L-65-N DIMENSIONS

Length.....22"
Width.....8"
Height.....21"
Weight.....50 lbs.



FEATURES

- Load steps: 1,2,2, 5, 10, 10, 20KW @208VAC Three Phase
- Load steps: .66,1.32,1.32, 3.3, 6.6, 6.6, 13.3KW @240VAC single phase
- Load steps: .33,.66,.66, 1.7, 3.3, 3.3,6.6KW @120VAC single phase
- The three lines (L1,L2,L3) can be tied to line on 120vac for 50kw load
- Plug test pins for connecting test leads
- Receptacle for ten foot cable(included with load bank)
- Meter- Digital Meter with three line display
- Power indicator lights
- Thermal protection
- Carrying case
- Folding handle

WEBSITE: WWW.CANNONLOADBANKS.COM